

### RESILIENT TYRES - LOADER GRIP

Tyre Size	Rim Size	EASY FIT/ NORMAL	Tread Pattern {Smooth(SM)/ Traction(TR)}	Tyre Dimension				Load Capacity (kg)			Finished tyre weight(kg)	Pcs/20ft
				Inch		mm		Trailers/ Skid Loaders				
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h		
17.5 - 25	14.00 - 25	N	LOADER GRIP (TR)	17.3	52.8	440	1340	9680	8800	8000	518	20
20.5 - 25	17.00 - 25	N	LOADER GRIP+ (TR)	20.7	58.7	525	1490	10890	9900	9000	788	16
20.5 - 25	17.00 - 25	N	LOADER GRIP (SM)	20.7	57.9	525	1470	10890	9900	9000	803	16
23.5 - 25	19.50 - 25	N	LOADER GRIP/GRIP+ (TR)	22.8	63.4	580	1610	12100	11000	10000	1076	16
23.5 - 25	19.50 - 25	N	LOADER GRIP (SM)	22.8	62.6	580	1590	12100	11000	10000	1082	16

### RESILIENT TYRES - SOLID GRIP

Tyre Size	Rim Size	EASY FIT/ NORMAL	Tread Pattern {Smooth(SM)/ Traction(TR)/ Rib(R)} (APP - Aperture ) (ND- Non Directional)	Tyre Dimension				Load Capacity (kg)			Finished tyre weight(kg)	Pcs/20ft
				Inch		mm		Other Vehicles (Trailers)				
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h		
13.00 - 24	8.50 - 24	N	SKS - APP 2FA	12.8	50.4	325	1280	7700	7000	6350	287	49
14.00 - 24	8.50 - 24	N	SKS - APP 2FA	13.9	52.4	352	1332	11100	10100	9300	325	30
13.00 - 24	8.50 - 24	N	SKS - APP 2FA - Triangular	12.8	50.4	325	1280	7700	7000	6350	287	49