

LAUGFS XTRALIFT PNEUMATIC FORKLIFT TYRES



LAUGFS XTRALIFT TYRES are designed with heavy-duty carcass and high abrasion-resistant tread, delivering both incredible puncture resistance and longer life.



LAUGFS
INDUSTRIAL TYRES



XTRALIFT

Reinforced sidewall for side impact protection and extra performance features make the tyre unstoppable. Its unique tread design delivers a smooth, comfortable ride with exceptional overall tyre life, while providing superior endurance and durability.

- The deep tread with extra thick sidewalls and strong casing
Provide exceptional durability and minimize the risk of punctures and accidental damages.
- Natural rubber based tread compound with right blend of reinforcing materials
Provides greater chip and tear /chunking resistance.
- Specially designed rim guard
Ensures protection against flat and wheel damages in the rim flange area.

LAUGFS XTRALIFT											
Tire Size	PR	Rim Width (inch)	TT / TL	Section Width		OD		Load Capacity (kg)		Inflation Pressure (psi)	Speed (kmph)
				mm	inch	mm	inch	Load Wheel	Steering wheel		
5.00-8	8	3	TT	134	5.3	472	18.6	-	830	115	25
5.00-8	10	3	TT	134	5.3	472	18.6	1415	1091	145	25
18x7-8	16	4.33	TT	168	6.6	465	18.3	2145	1640	145	25
6.00-9	10	4	TT	164	6.5	549	21.6	1515	1280	125	25
6.50-10	12	5	TT	183	7.2	596	23.5	1935	1635	140	25
7.00-12	14	5	TT	192	7.6	690	27.2	2670	2255	145	25
250-15	18	7.5	TT	250	9.8	735	28.9	4105	3470	150	25
300-15	20	8	TT	300	11.8	840	33.1	5940	4990	135	25
7.00-15	14	6	TT	203	8.0	758	29.8	3090	2610	145	25
7.50-15	14	6	TT	205	8.1	772	30.4	3505	2965	140	25
28x9-15 / 8.15 - 15	14	7	TT	225	8.9	716	28.2	3075	2595	140	25
8.25-15	14	6.5	TT	242	9.5	852	33.5	3830	3235	120	25
8.25-15	16	6.5	TT	242	9.5	852	33.5	4615	3550	131	25
10.00-20	18	7.5	TT	284	11.2	1080	42.5	-	6900	145	30
12.00-20	20	8.5	TT	320	12.6	1151	45.3	9231	7101	145	25